



Manually operated-lubrication system

18 kg-BE-Ø 240-290 mm-SRL 510

Item number: 17 618
EAN: 4103810176180
Discount group: A

Technical data

Pumping media: lubricating greases, up to NLGI 2
Delivery rate to refill grease gun / stroke (cm³): 30
Length of discharge hose (mm): 1500
Grease supply into the hand operated grease gun: manually lever operated
Follower plate: for 18 kg container
Ø follower plate (mm): 240 – 290
Length of suction tube (mm): 510
Connection hose/one hand grease gun: quick release adapter Rectus, type 26 (17 601), with nonreturn valve
Delivery rate EHFP / stroke (cm³): 0,4
Discharge pressure up to (bar): 550
Burst pressure EHFP (bar): 850
Burst pressure grease gun head (bar): 1200
Capacity EHFP (cm³): 125
Grease gun connection, pressure-side: M 10 x 1
Grease pump piston actuation: manual, by means of pressure grip
Material pump body: steel
Material pump head: impact-resistant zinc die casting
Surface treatment: all steel components are galvanized
Lacquering dust cover: blue, Pantone 294 C

Specification

- Manual pump to refill one hand operated grease gun
- Pump
- Suction tube
- Dust cover (17 176), stabilising-fixing bracket (17 197) and follower plate (17 275)
- One hand operated grease gun (EHFP), connection M 10 x 1 (17 600)
- Spout, straight, M 10 x 1, 150 mm (12 435)
- Coupler, 4 jaws, M 10 x 1 (12 631)
- Discharge hose (17 003)
- Packed in single carton box

Packaging

Dimensions packaging LxWxH (mm): 670 x 420 x 100
Weight including package (kg): 5,5
Packing unit: 1.0