



PREMAxx 38 l/min-10 gpm
12 V-DC-ABK-ZVPP-4 m

Item number: 23 711
EAN: 4103810237119
Discount group: D

Technical data

Connecting cable with battery terminal clips, length (m) / (ft): 2 / 6.6
Connection container: G 2" male, drum adapter
Connection suction side: Hose fitting DN 19
Connection discharge side: G 1" male
Hydraulic data
Pump design: axial gear
Delivery rate under free discharge up to (l/min) / (gpm): 38 / 10
Suction height up to (m) / (ft): 2,5 / 8.2
Discharge height max. (m) / (ft): 15 / 49.2
Pumping media: fuel oil and diesel
Motor data
Voltage (V): 12 V DC
Power consumption (A): 14
Power (W): 180
Thermal protection: self resetting
Duty cycle (min): 30
Rotation speed at 0,5 bar counterpressure (rpm): 7500
Type of construction: IMB 5
Protection class: IP 34
Material of pump housing and pump: PA 6
Dimensions of pump LxWxH (mm) / (inch): 90 x 120 x 300 / 3.5 x 4.7 x 11.8
Weight with accessories (kg) / (lb): 4,5 / 9.9

Specification

- For 200 up to 1000 l container
- Axial wheel pump with manual pump assembly (23 710)
- Illuminated on/off switch
- Motor with thermal protection switch, self resetting
- Siphon protection acc. to WHG (German government regulation for environmental care), continuously active
- Discharge hose, 4 m / 13,1 ft, DN 19, G 1" male, G 1" female (23 144)
- Polypropylene nozzle valve, ZVPP (23 161)
- Suction hose, 1,6 m / 5,2 ft, with brass strainer
- Barrel screw coupling, G 2" male
- Valuable sales package

Special notes

- The pump is lightweight and very quiet in operation.
- Resistant against small dirt particles in the liquid to be discharged
- The liquid column is to be established via manual pumping
- Can be manually operated in case of electric power blackout
- Pump can only be utilized as barrel pump
- Replace the carbons when the pump has delivered a volume of 100,000 l

Packaging

Dimensions LxWxH (mm) / (inch): 400 x 400 x 220 / 15.7 x 15.7 x 8.7
Weight including package (kg) / (lb): 5,31 / 11.7
Packing unit: 1.0