



**Mechanical nozzle valve**

AdBlue®/DEF-G 1" female-60 l/min-PP

**Item number:** 23 163 878  
**EAN:** 4048358709769  
**Discount group:** D

**Technical data**

**Connection:** G 1" male with hose fitting, NW 19 mm / 0.75 inch  
**Flow capacity max. (l/min) / (gpm):** 60 / 15  
**Outside diameter discharge tube (mm) / (inch):** 18 / 0.7  
**Switch-off:** manual  
**Working pressure (bar) / (psi):** 0,5 - 4 / 7.3 - 58  
**Operating pressure max. (bar/psi):** 4 / 58

**Materials of parts in contact with liquid**

**Casing:** plastic  
**Discharge:** stainless steel  
**Piston:** POM  
**Pressure spring:** stainless steel  
**Seals:** FKM  
**Nipple:** PA 6 GF 30  
**Union nut:** PA 6 GF 30  
**Cap:** plastic

**Dimensions LxWxH (mm) / (inch):** 330 x 170 x 50 / 12.99 x 6.69 x 1.97  
**Weight (kg) / (lb):** 0,53 / 1.17

**Specification**

- Mechanical control nozzle for AdBlue®
- Note in the case of the formation of crystals: To dissolve the crystals, bring the AdBlue® nozzle in the compressed (open) position and put it in hot water for half an hour (max. 50 °C / 122 °F)

**Packaging**

**Dimensions LxWxH (mm) / (inch):** 400 x 170 x 60 / 15.75 x 6.69 x 2.36  
**Weight including package (kg) / (lb):** 0,53 / 1.17  
**Packing unit:** 1,0