



### Venturi-waste oil suction unit-24 I

mobile

**Item number:** 19 782

**EAN:**

**Discount group:** D

#### Technical data

Total volume (l): 24

Compressed air connection: Male quick release adapter, for Rectus coupling, type 26, NW 7,2 mm

Recommended air pressure (bar): 6

Vacuum generation time (min): 1 - 2

Suction volume per vacuum build up (l): 8 - 12

Suction rate probe Ø 5 mm (l/min): 1,0 - 1,5

Suction rate probe Ø 6 mm (l/min): 2,0 - 2,5

Suction rate probe Ø 8 mm (l/min): 3,5 - 4,0

Min. oil temperature: 70

Lacquering of container: window grey, satin, RAL 7040

Media: for waste oils of hazard class A III of known origin with flash points higher than 55°C; or not easily inflammable liquids, not suitable for highly inflammable liquids

Dimensions LxWxH (mm): 380 x 380 x 950

#### Specification

- A vacuum is generated in the container by means of a venturi system and compressed air
- Manometer, for pressure indication
- Suction is done via the dipstick tube.
- Male quick release adapter, for Rectus coupling, type 26, NW 7,2 mm
- Suction probes, Ø 5 / 6 / 8 mm
- With adapters for BMW, Mercedes, VW and Audi
- Carrying handle
- Hose, 1700 mm
- 2 fixed rear wheels
- Drainage via screw cap, G 1 1/2"

#### Special notes

- The units are subject to the German government regulation for pressurized containers classification group 1 (max. pressure 0,5 bar to drain a waste oil unit)

#### Packaging

Dimensions LxWxH (mm): 380 x 360 x 950

Weight (kg): 9,94

Packing unit: 1.0