



### Waste oil suction system-stat.

PNP 5:1-suction hose-2 m

**Item number:** 19 800

**EAN:**

**Discount group:** D

#### Technical data

Compressed air connection: G 1/4" female  
Discharge: via pneumatic pump 5:1  
Connection suction hose: hydraulic coupling, size 4, G 3/4" female  
Connection discharge side: G 3/4" male  
Media: for waste oils of hazard class A III of known origin with flash points higher than 55°C; or not easily inflammable liquids, not suitable for highly inflammable liquids

Weight (kg): 9,14

#### Specification

- Stationary, for drainage of waste oil drainers (27 035), (27 035 890) or (19 857)
- For direct discharge to a waste oil collecting tank via pipe line
- Suction hose, 2 m, with inline filters and hydraulic coupling, size 4, G 3/4" female (19 770)
- Pneumatic oil pump 5:1 (19 385)
- Wall mounting bracket (19 521)
- Complete with accessories for assembly
- Female quick release connector, size 4, G 3/4" (19 774)
- Suitable for garage service pit drainage trays

#### Special notes

- Waste oil must not be stored in working areas. It is recommended acc. to German govt. specification to install an overflow protection valve if waste oil discharge shall be effected by using a fixed pipe-work installation. Adhere to regional regulations and guidelines in any case.

#### Packaging

Dimensions LxWxH (mm): 400 x 360 x 150

Weight (kg): 9,6

Packing unit: 1.0