



Waste oil drainer/-suction unit-90 I

mobile-pneumatic pump 1:1

Item number: 27 410 890

EAN:

Discount group: D

Technical data

Total volume (l):	95
Telescopic height level of drain bowl (mm):	1340 - 1910
Diameter drain bowl (mm):	420
Volume of drain bowl (l):	18
Compressed air connection:	Male quick release adapter, for Rectus coupling, type 26, NW 7,2 mm
Discharge:	via pneumatic pump 1:1
Connection drainage:	hydraulic coupling, size 4, G 3/4" female
Suction rate probe Ø 6 mm (l/min):	2,0 - 2,5
Suction rate probe Ø 8 mm (l/min):	3,5 - 4,0
Min. oil temperature:	70
Lacquering of container:	window grey, satin, RAL 7040
Lacquering of drain bowl:	blue, Pantone 294 C
Media:	for waste oils of hazard class A III of known origin with flash points higher than 55°C; or not easily inflammable liquids, not suitable for highly inflammable liquids
Dimensions LxWxH (mm):	600 x 580 x 1310
Suction rate probe Ø 5 mm (l/min):	1,0 - 1,5

Specification

- Pneumatic pump 1:1, with inline filter mounted on suction side, male quick connecting adapter, for quick connecting couplers, type 26 (20 062)
- Float full level indicator
- 3 way lever ball valve
- Suction hose, 2 m, with spiral spring
- Suction probe holder
- Suction probes, Ø 5 / 6 / 8 mm
- With adapters for BMW, Mercedes, VW, Audi and Smart
- Discharge hose, 2 m, with hydraulic coupling, size 4 (19 770) and
 - connecting plug, size 4 (19 774), fixed on a container as a counterpart
 - connecting plug, size 4 (19 774), enclosed without package, for connection to oil distribution lines or to waste oil collecting tanks
- Drain bowl with removable strainer and drain grill
- Sturdy handle
- 2 fixed rear wheels, 2 castor front wheels
- Container, made from 1,5 mm sheet steel
- With metal protective cover to avoid damage
- Lacquered with oil-resistant hydro-structure paint
- With height adjustable drain bowl

Special notes

- The units are subject to the German government regulation for pressurized containers classification group 1 (max. pressure 0,5 bar to drain a waste oil unit)
- If the waste oil drainer is discharged via a pipe system into an oil collection tank, it is recommended to use an overflow protection valve. Please adhere to regional regulations and guidelines of your country

Packaging

Dimensions LxWxH (mm):	630 x 580 x 1000
Weight (kg):	42
Packing unit:	1.0

