



PREMAxx 52 l/min

230 V-1~AC-50 Hz-EUS-ZVPP-4 m

Item number: 23 731
EAN: 4103810237317
Discount group: D

Technical data

Connecting cable with Euro two-pin plug,
length (m): 2
Connection container: G 2" male, drum adapter
Connection suction side: Hose fitting DN 19
Connection discharge side: G 1" male
Hydraulic data
Pump design: axial gear
Delivery rate under free discharge
(l/min): 52
Suction height (m): 2
Flow media: fuel oil and diesel
Motor data
Voltage (V): 230
Frequency (Hz): 50
Power consumption (A): 1,8
Power (kW): 0,32
Thermal protection: self resetting
Duty cycle (min): 30
Rotation speed at 0,5 bar
counterpressure (rpm): 7500
Type of construction: IMB 5
Protection class: IP 34
Material of pump housing and pump: PA 6
Dimensions of pump LxWxH (mm): 90 x 120 x 350
Weight with accessories (kg): 4,26

Specification

- For 200 up to 1000 l container
- Axial wheel pump with manual pump assembly (23 730)
- Illuminated on/off switch
- Motor with thermal protection switch, self resetting
- Siphon protection acc. to WHG (German government regulation for environmental care), continuously active
- Discharge hose, 4 m, DN 19, G 1" male, G 1" female (23 144)
- Polypropylene nozzle valve, ZVPP (23 161)
- Suction hose, 1,6 m, with brass strainer
- Drum adapter, PA, G 2" male and M 64 x 4 male
- Valuable sales package

Special notes

- The pump is lightweight and very quiet in operation.
- Resistant against small dirt particles in the liquid to be discharged
- The liquid column is to be established via manual pumping
- Can be manually operated in case of electric power blackout
- Pump can only be utilized as barrel pump
- Replace the carbons when the pump has delivered a volume of 100,000 l

Packaging

Dimensions LxWxH (mm): 400 x 400 x 220
Weight including package (kg): 5,2
Packing unit: 1.0